



## Product description

Fingerprint module as access control system with function LED.

Performance features:

- Not backwards-compatible with the FPM 611-02
- Stand-alone operation
- Up to 100 user fingerprints
- Up to 5 user groups
- Capacitive line sensor

## Specifications

Operating voltage:	12 V AC, 12–30 V DC
Operating current:	120 mA AC, 70 mA DC
Contact type:	contact 24 V, 2 A
Switching time:	3 sec
Protection system:	IP 54
Ambient temperature:	–20 °C to +55 °C
Height of structure (mm):	17
Dimensions (mm) W x H x D:	99 x 99 x 43

## Article information

Article designation	Article description	Colour/Material	KG SAP article no.
FPM 600-0 AG	Fingerprint module	Anthracite grey	D 210009608-00
FPM 600-0 DG	Fingerprint module	Micaceous dark grey	D 210009609-00
FPM 600-0 SM	Fingerprint module	Silver metallic	D 210009610-00
FPM 600-0 W	Fingerprint module	White	D 210009607-00



Fingerprint module  
FPM 600-0

Page 2

---

## Accessories

---

Article designation	Article description	Colour/Material	KG SAP article no.
Vario 611 AG	Touch-up applicator	Anthracite grey	0 210007124-00
Vario 611 DG	Touch-up applicator	Micaceous dark grey	0 210007123-00
Vario 611 SM	Touch-up applicator	Silver metallic	0 210007117-00
Vario 611 W	Touch-up applicator	White	0 210007116-00

---

## Spare parts

---

Article designation	Article description	Colour/Material	KG SAP article no.
FPM 611-...	Terminal block	Black	E 200029928-00
Vario 611	Sealing frame modules	Grey	E 210007484-00

Fingerprint module  
FPM 600-0

Page 3





Fingerprint module  
FPM 600-0

Page 4

---

FPM 600-0 Fingerprint module	Product information	958 kB	Download
FPM 6xx-... Fingerprint table	Programming template	85,7 kB	Download
FPM 600-...	Declaration of Conformity	762 kB	Download
	Additional information	140 kB	Download
	System manual	5,9 MB	Download