

Storey controller  
ETC 602-0

200015370-00



## Product description

Storey controller in switch panel housing for connection of an additional storey door loudspeaker to the relevant system telephones HTS/HTC 811-...

Several storey controllers can be used in one system. Several calls are possible simultaneously, e.g. from the main entrance door loudspeaker to an in-house telephone and simultaneously from the storey door loudspeaker to a connected in-house telephone. Potential-free changeover contact WT/W0/WE e.g. for switchover from the door to the storey camera.

## Specifications

Operating voltage:	24 V DC
Operating current:	max. 60 mA
Contact type:	changeover switch max. 24 V, 2 A
Ambient temperature:	0 °C to +40 °C
Protection system:	IP 20
Horizontal pitch (HP):	6
Dimensions (mm) W x H x D:	107 x 89 x 60

## Article information

Article designation	Article description	Colour	KG SAP article no.
ETC 602-0	Storey controller	Black	A 200015370-00

Storey controller  
ETC 602-0

200015370

Page 2





Storey controller  
ETC 602-0

200015370

Page 3

---

ETC 602-0 Storey controller

ETC 602-...

Product information

296 kB

[Download](#)

Declaration of Conformity

126 kB

[Download](#)

Additional information

420 kB

[Download](#)