

Call controller
RC 602-0

200015980-00



Product description

Call controller in switch panel housing, for the conversion of coded calls to switching contacts in conjunction with the code lock module or display call module.

Up to 8 Siedle Vario door loudspeakers for code calls can be connected to an RC 602-... The call can be initiated either at the keypad of a code lock module or at the display call module from a door loudspeaker. The RC 602-... converts the code calls and makes available 8 call outputs for 8 users. By series connection with up to 31 RCE 602-... units, a maximum of 504 call outputs/users can be connected. At the door loudspeaker, direct calls can also be placed using call buttons.

Specifications

Operating voltage:	12 V AC
Operating current:	max. 180 mA
Contact type:	8 n.o. contacts 24 V, 1 A
Ambient temperature:	0 °C to +40 °C
Protection system:	IP 20
Horizontal pitch (HP):	6
Dimensions (mm) W x H x D:	107 x 89 x 60

Article information

Article designation	Article description	Colour/Material	KG SAP article no.
RC 602-0	Call controller	Black	B 200015980-00

Accessories

Article designation	Article description	Colour/Material	KG	SAP article no.
RCC 602-0	Call controller card	White	B	200017885-00
RCE 602-0	Call controller extension	Black	B	200015960-00
ZRCE 602-0	Ribbon cable	Others	B	200017875-00

Call controller
RC 602-0

200015980

Page 2





Call controller
RC 602-0

200015980

Page 3

RC 602-0 Call Controller

RC 602-...

Product information

1,1 MB

[Download](#)

Declaration of Conformity

132 kB

[Download](#)

Additional information

140 kB

[Download](#)