



Lock module  
SM 611-01 SM  
200019402-01

## Product description

Lock module with two-stage non-holding contact for accommodating a customer-provided profile half cylinder in accordance with DIN 18252 with a total length of approx. 40 mm. The lock ward can be fixed or adjustable.

## Specifications

|                            |                   |
|----------------------------|-------------------|
| Contact type:              | contact 24 V, 2 A |
| Mounting depth (mm):       | 41                |
| Protection system:         | IP 54             |
| Ambient temperature:       | -20 °C to +55 °C  |
| Height of structure (mm):  | 9                 |
| Dimensions (mm) W x H x D: | 99 x 99 x 50      |

## Article information

| Article designation | Article description | Colour/Material | KG SAP article no. |
|---------------------|---------------------|-----------------|--------------------|
| SM 611-01 SM        | Lock module         | Silver metallic | B 200019402-01     |


## Accessories

| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|---------------------|-----------------|----|-----------------|
| Vario 611 SM        | Touch-up applicator | Silver metallic | 0  | 210007117-00    |

Lock module  
SM 611-01 SM

200119402

Page 2





Lock module  
SM 611-01 SM

200119402

Page 3

---

SM 611-01 Lock module

Product information

536 kB

[Download](#)

Declaration of Conformity

140 kB

[Download](#)

SM 611-01

Declaration of Conformity

333 kB

[Download](#)

Additional information

140 kB

[Download](#)