

Line rectifier
NG 402-03

200033590-00



Product description

Line rectifier for 6+n technology and for P.O. amplifier unit PVG 402-...

Specifications

Operating voltage:	230 V AC, +/-10 %, 50/60 Hz
Operating current:	200 mA
Output voltage:	8.3 V DC stabilized, 12 V AC
Output current:	2 A AC, 0.4 A DC
Fusing:	primary Si1 T 200 mA L
Protection system:	IP 20
Ambient temperature:	0 °C to +40 °C
Horizontal pitch (HP):	6
Dimensions (mm) W x H x D:	107 x 89 x 60

Article information

Article designation	Article description	Colour/Material	KG SAP article no.
NG 402-03	Line rectifier	Black	A 200033590-00

Spare parts


Article designation	Article description	Colour/Material	KG	SAP article no.
NG 402/602-...	Fuse holder	Others	E	210005106-00
T 0,2 A/250 V	fuse 5 x 20 mm	Others	E	210007481-00
T 0,63 A/250 V	fuse 5 x 20 mm	Others	E	210007482-00

Line rectifier
NG 402-03

200033590

Page 2





Line rectifier
NG 402-03

200033590

Page 3

NG 402-03 Line rectifier	Product information	378 kB	Download
NG 402-... Line rectifier	Declaration of Conformity	997 kB	Download
Door and In-House Communication Part 1, edition A Planning and Installation 6+n	Planning Guide	4,4 MB	Download
Door and In-House Communication Part 2, edition A Explanation on planning and Installation 6+n	Planning Guide	4,7 MB	Download
	Additional information	140 kB	Download