



Door loudspeaker
module
TLM 612-02 GM
200036807-00

Product description

Door loudspeaker module 1+n technology for Siedle Vario with integrated loudspeaker and microphone.

Performance features:

- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone
- Potential-free light button with LED-lit light symbol
- Work contacts for light and door release, can be controlled without additional wiring via existing side circuit
- An SFC 602-... switching/remote controller and/or CTÖ 602-... controller door release can be connected
- A COM 611-... code lock module and/or DRM 612-... display call module for digital call input can be connected
- Acoustic feedback when pressing a call button can be activated

Specifications

Contact type:	2 n.o. contacts 24 V, 2 A
Switching time:	3 sec
Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54
Height of structure (mm):	9
Dimensions (mm) W x H x D:	99 x 99 x 35

Article information

Article designation	Article description	Colour	KGSAP article no.
TLM 612-02 GM	Door loudspeaker module	Graphite brown metallic	D 200036807-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 GM	Touch-up applicator	Graphite brown metallic	0	210007119-00

Spare parts



Door loudspeaker
module
TLM 612-02 GM

200036807

Page 2

Article designation	Article description	Colour	KG	SAP article no.
BTLE 050-.../-03, BTLM 650-..., TLM 611/612-...	Loudspeaker	Others	E	200029074-01
TLM 611/612-02, BTLM 650-04/651-0, ATLM 670/671-0	Microphone	Others	E	210011867-00
TLM 612-...	Terminal block	Black	E	210007290-00
TLM 61x-01, BTLM 650-... GM	Light button with light symbol	Graphite brown metallic	E	200029097-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Door loudspeaker
module
TLM 612-02 GM

200036807

Page 3





Door loudspeaker
module
TLM 612-02 GM

200036807

Page 4

TLM 612-...

Declaration of Conformity

3,2 MB

[Download](#)

Additional information

420 kB

[Download](#)

System manual

2,5 MB

[Download](#)