



LED surface area light
LEDF 600-4/3-0 SM

200037481-00

Product description

LED surface area light for illumination of inscriptions and the door station, with integrated info sign for large-scale display of all types of information (such as street, company, logo).

No mounting frame required. For optimum inscription possibilities please use the Siedle lettering service.

Specifications

| | |
|----------------------------|------------------|
| Operating voltage: | 20–30 V DC |
| Operating current: | max. 335 mA |
| Colour temperature: | 6000 K |
| Light intensity: | 486 cd/klm |
| Luminous flux: | 194 lm |
| Protection system: | IP 54 |
| Ambient temperature: | –20 °C to +55 °C |
| Dimensions (mm) W x H x D: | 399 x 299 x 50 |

Article information

| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|------------------------|-----------------|----|-----------------|
| LEDF 600-4/3-0 SM | LED surface area light | Silver metallic | D | 200037481-00 |

Accessories

| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|--|-----------------|----|-----------------|
| MA/LEDF 600-0 | Mounting adapter for LED surface light | Black | D | 200037350-00 |
| Vario 611 SM | Touch-up applicator | Silver metallic | 0 | 210007117-00 |

Spare parts

| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|---------------------|-----------------|----|-----------------|
| LEDM/LEDF 600-... | Terminal block | Black | E | 200029930-00 |

LED surface area light
LEDF 600-4/3-0 SM

200037481

Page 2





LED surface area light
LEDF 600-4/3-0 SM

200037481

Page 3

LEDF 600-... LED surface area light
Information and tips on care and cleaning
LEDF 600-...

| | | |
|---------------------------|---------|--------------------------|
| Product information | 1,3 MB | Download |
| Product information | 327 kB | Download |
| Declaration of Conformity | 97,6 kB | Download |
| Additional information | 140 kB | Download |