



Access door  
loudspeaker module  
ATLM 670-0 W

200041755-00

## Product description

Access door loudspeaker module for Siedle Vario with integrated loudspeaker and microphone.

### Performance features:

- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone
- Light button with LED-lit light symbol
- Connection of a ZAM 670-... status display module for optical and acoustic signalling of the operating state
- Acoustic feedback when pressing a call button can be activated

Up to max. 48 call button modules can be connected in any combination, allowing up to max. 192 call buttons to be connected.

## Specifications

Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54
Height of structure (mm):	9
Dimensions (mm) W x H x D:	99 x 99 x 35

## Article information

Article designation	Article description	Colour	KG	SAP article no.
ATLM 670-0 W	Access door loudspeaker module	White	F	200041755-00

## Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 W	Touch-up applicator	White	0	210007116-00

## Spare parts

Article designation	Article description	Colour	KG	SAP article no.
ATLE/CATLE/ATLM/SATLM 670-...	Loudspeaker	Others	E	210011868-00



Access door  
loudspeaker module  
ATLM 670-0 W

200041755


Page 2

Article designation	Article description	Colour	KG	SAP article no.
ATLM 67x-...	Terminal block	Black	E	200029835-00
TLM 611/612-02, BTLM 650-04/651-0, ATLM 670/671-0	Microphone	Others	E	210011867-00
TLM 61x-01, BTLM 650-... W	Light button with light symbol	White	E	200029096-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Access door  
loudspeaker module  
ATLM 670-0 W

200041755

Page 3





Access door  
loudspeaker module  
ATLM 670-0 W

200041755

Page 4

---

ATLM 671-0 Access door loudspeaker module Plus

ATLM 670-0 Access door loudspeaker module

Product information

499 kB

[Download](#)

Declaration of Conformity

218 kB

[Download](#)

Commissioning instruction

2,2 MB

[Download](#)

Commissioning instruction

2 MB

[Download](#)

Additional information

420 kB

[Download](#)

System manual

8 MB

[Download](#)