SSS SIEDLE

Display call module
DRM 612-02 W

200048756-02

Product description

Display call module as an input device with 4-line display for placing door calls.

Customer-specific data stored in the DRM 612-… is indicated on the display. To scroll in the name segment / name index, there are two arrow keys provided for “up/down”.
When the required name is marked in the list, pressing the OK button will initiate a call to this user.
An external DR button can be connected
• 4-line display with white LED background lighting
• 3 highly sensitive stroke-free piezo buttons
• Button actuation with acoustic acknowledgement
• Backlit symbols
• Up to max. 504 users can be programmed
Programming possibilities:
• Using a PC and the programming software PRS 602-… via programming interface PRI 602-… USB
• or manually using the buttons at the DRM 612-…

Specifications

Operating voltage:	12 V AC
Operating current:	max. 200 mA
Protection system:	IP 54
Ambient temperature:	–20 °C to +55 °C
Dimensions (mm) W x H x D:	99 x 99 x 27

Article information

Article designation	Article description	Colour	KG	SAP article no.
DRM 612-02 W	Display call module	White	D	200048756-02

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 W	Touch-up applicator	White	0	210007116-00

Display call module
DRM 612-02 W

210010360

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
DRM 612-...	Terminal block	Black	E	210010988-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Display call module
DRM 612-02 W

210010360

Display call module
DRM 612-02 W

210010360

DRM 612-02 Display call module	Product information	5 MB	Download
	Declaration of Conformity	140 kB	Download
PRS 602-02 V5.5.1.1 Vario bus programming software	Software	138 MB	Download
	Commissioning instruction	756 kB	Download
REACH Information	Additional information	798 kB	Download