

Display call module
 DRM 612-02 W
 200048756-02



Product description

Display call module as an input device with 4-line display for placing door calls.

Customer-specific data stored in the DRM 612-... is indicated on the display. To scroll in the name segment / name index, there are two arrow keys provided for "up/down".

When the required name is marked in the list, pressing the OK button will initiate a call to this user.

An external DR button can be connected

- 4-line display with white LED background lighting
- 3 highly sensitive stroke-free piezo buttons
- Button actuation with acoustic acknowledgement
- Backlit symbols
- Up to max. 504 users can be programmed

Programming possibilities:

- Using a PC and the programming software PRS 602-... via programming interface PRI 602-... USB
- or manually using the buttons at the DRM 612-...

Specifications

Operating voltage:	12 V AC
Operating current:	max. 200 mA
Protection system:	IP 54
Ambient temperature:	-20 °C to +55 °C
Dimensions (mm) W x H x D:	99 x 99 x 27

Article information

Article designation	Article description	Colour	KG	SAP article no.
DRM 612-02 W	Display call module	White	D	200048756-02

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 W	Touch-up applicator	White	0	210007116-00



Display call module
DRM 612-02 W

210010360

Page 2

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
DRM 612-...	Terminal block	Black	E	210010988-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Display call module
DRM 612-02 W

210010360

Page 3





Display call module
DRM 612-02 W

210010360

Page 4

DRM 612-02 Display call module	Product information	5 MB	Download
	Declaration of Conformity	140 kB	Download
PRS 602-02 V5.5.1.1 Vario bus programming software	Software	138 MB	Download
	Additional information	420 kB	Download