

System-free camera 180
for Siedle Vario
CM 618-02 SM
200049360-01

Product description

System-free camera 180 for Siedle Vario with automatic day/night switchover (True Day/Night) and integrated infrared lighting. Horizontal/vertical pick-up angle: appr. 175°/120°

Full screen or 9 picture excerpts can be selected
Electronic image rectification in full screen
Extended pick-up angle in edge area for selected picture excerpt
Backlight compensation (BLC)
Wide Dynamic Range (WDR)
Colour system: PAL
Image pick-up: CMOS sensor 1/2.7" 1920 x 1080 pixels
Resolution: 600 TV lines
Lens: 1.55 mm
Continuous operation: suitable
2-step heating: 12 V AC max. 130 mA
Video output: 1 V_{ss} at 75 Ohm

Specifications


Operating voltage:	10–50 V DC
Operating current:	max. 210 mA
Protection system:	IP 54, IK 10
Ambient temperature:	–20 °C to +55 °C
Height of structure (mm):	15
Dimensions (mm) W x H x D:	99 x 99 x 41

Article information

Article designation	Article description	Colour	KGSAP article no.
CM 618-02 SM	System-free camera 180 for Siedle Vario	Silver metallic	D 200049360-01

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 SM	Touch-up applicator	Silver metallic	0	210007117-00




System-free camera 180
for Siedle Vario
CM 618-02 SM

210009596

Page 2

Spare parts


Article designation	Article description	Colour	KG	SAP article no.
ACM 671/673/678-..., BCM 65x-..., CM 61x-...	Glass cover	Clear glass	E	200048697-00
ACM 671/673/678-..., BCM 65x-..., CM 61x-... SM	Screen frame	Silver metallic	E	200048699-00
BCM 65x-..., BCMx 650-...	Terminal block	Black	E	200029921-00
CMx 612-..., CM 611-...	Terminal block	Black	E	200029922-00
Vario 611	Sealing frame modules	Grey	E	210007484-00




System-free camera 180
for Siedle Vario
CM 618-02 SM

210009596

Page 3





System-free camera 180
for Siedle Vario
CM 618-02 SM

210009596

Page 4

Camera 130/180	Product information	1,3 MB	Download
CM 618-... Camera module 180	Declaration of Conformity	3,5 MB	Download
	Additional information	420 kB	Download