

DoorCom ISDN Set  
DCA/IT 740-0 Set

200086730-00



## Product description

DoorCom analogue set for Siedle Multi comprising two individual devices in switch panel housing.

The universal a/b interface links Siedle door and in-house telephony to the public network at the standardized a/b interface of the telephone network or at the relevant TC system output. With display and 6 buttons for configuration. In relation to the door station, it acts in the same way as 4 Multi telephones.

Performance features.

- System functions door release and light using the DTMF dialling method
- Per DCA 740-... set, 1-4 call destinations possible
- Max. 9 control functions can be executed via FSM 740-... by means of DTMF dialling
- 3 transistor outputs for AR 85052-10 or AR 85911-10 freely programmable with status enquiry. The outputs can be used for doormatic status display, single concierge or as a switching function.
- 3 potential-free outputs can be used for door release, storey calls, call silencing and single concierge functions.
- Selective dialling of max. 6 door loudspeakers via code speed dial
- Selective dialling of the door which made the last call
- Doormatic function per user
- Assignable call number (max. 22-digit)
- Direct calls, selective user calls to PBX extensions, to the public network or mobile networks, chain calls on no answer or engaged
- Day/night service switching to alternative call destinations (depending on existing TC system on site)
- Switching from door intercom to telephone mode
- Several DCAs possible in one intercom system/in one TC system
- Adjustable call and connection time
- Signalling of door calls prior to call acceptance
- Call differentiation when using two DCA 740-... sets possible.
- PIN protection can be activated, e.g. for programming, door release, switching functions and function activation.

## Specifications

Scope of supply:	DCA 740#0 and IT 740#0
Operating voltage:	24 V DC
Protection system:	IP 20
Ambient temperature:	0 °C to +40 °C
Horizontal pitch (HP):	6/6
Dimensions (mm) W x H x D:	107 x 89 x 60

## Article information



DoorCom ISDN Set  
DCA/IT 740-0 Set

200086730

Page 2

**Article designation**  
DCA/IT 740-0 Set

**Article description**  
DoorCom ISDN Set

**Colour**  
Others

**KG SAP article no.**  
E 200086730-00

DoorCom ISDN Set  
DCA/IT 740-0 Set

200086730

Page 3





DoorCom ISDN Set  
DCA/IT 740-0 Set

200086730

Page 4

---

	Product information	382 kB	<a href="#">Download</a>
DCA 740-01 DoorCom®-Analog Operating instructions	Manual	178 kB	<a href="#">Download</a>
	Manual	22,4 kB	<a href="#">Download</a>
DCA-IT 740-...	Declaration of Conformity	352 kB	<a href="#">Download</a>
	Additional information	420 kB	<a href="#">Download</a>