

200086730-00



Product description

DoorCom analogue set for Siedle Multi comprising two individual devices in switch panel housing.

The universal a/b interface links Siedle door and in-house telephony to the public network at the standardized a/b interface of the telephone network or at the relevant TC system output. With display and 6 buttons for configuration. In relation to the door station, it acts in the same way as 4 Multi telephones. Performance features.

- System functions door release and light using the DTMF dialling method
- Per DCA 740-... set, 1-4 call destinations possible
- Max. 9 control functions can be executed via FSM 740-... by means of DTMF dialling
- 3 transistor outputs for AR 85052-10 or AR 85911-10 freely programmable with status enquiry. The outputs can be used for doormatic status display, single concierge or as a switching function.
- 3 potential-free outputs can be used for door release, storey calls, call silencing and single concierge functions.
- Selective dialling of max. 6 door loudspeakers via code speed dial
- Selective dialling of the door which made the last call
- Doormatic function per user
- Assignable call number (max. 22-digit)

• Direct calls, selective user calls to PBX extensions, to the public network or mobile networks, chain calls on no answer or engaged

- Day/night service switching to alternative call destinations (depending on existing TC system on site)
- Switching from door intercom to telephone mode
- Several DCAs possible in one intercom system/in one TC system
- Adjustable call and connection time
- Signalling of door calls prior to call acceptance
- Call differentiation when using two DCA 740-... sets possible.
- PIN protection can be activated, e.g. for programming, door release, switching functions and function activation.

| Scope of supply: | DCA 740#0 and IT 740#0 | |
|----------------------------|------------------------|--|
| Operating voltage: | 24 V DC | |
| Protection system: | IP 20 | |
| Ambient temperature: | 0 °C to +40 °C | |
| Horizontal pitch (HP): | 6/6 | |
| Dimensions (mm) W x H x D: | 107 x 89 x 60 | |
| | | |

Article information

Specifications

SSS SIEDLE

Page 2



Article designation DCA/IT 740-0 Set Article description DoorCom ISDN Set Colour/Material Others
 KG
 SAP article no.

 E
 200086730-00



200086730

Page 3







Page 4



DCA 740-01 DoorCom®-Analog Operating instructions

DCA-IT 740-...

| Product information | 382 kB | Download |
|---------------------------|---------|----------|
| Manual | 178 kB | Download |
| Manual | 22,4 kB | Download |
| Declaration of Conformity | 352 kB | Download |
| Additional information | 109 kB | Download |
| | | |