SSS SIEDLE

Door loudspeaker module Line Level
TLM/LL 611-02 SM

200087581-00

Product description

Door loudspeaker module Line-Level for Siedle Vario with integrated loudspeaker and microphone, for connection to a symmetrical or asymmetrical line interface, e.g. on DoorCom IP systems, IP servers as well as on IP telephone systems.

Performance features:
• Front grille made of weather and UV-resistant polycarbonate
• Loudspeaker, voice volume can be adjusted
• Durable electret microphone, microphone amplifier with volume control
• Potential-free light button with LED-lit light symbol
• Symmetrical or asymmetrical transmission of line signals can be performed (separate microphone and loudspeaker)
• Line-in 800 mVeff, impedance 2 kOhm
• Line-out 100 mVeff, impedance 100 Ohm
• Built-in echo cancellation for full-duplex operation
• Muting function

Specifications

Operating voltage:	15–28 V DC
Operating current:	max. 100 mA
Contact type:	contact 24 V, 2 A
Ambient temperature:	–20 °C to +55 °C
Dimensions (mm) W x H x D:	99 x 99 x 35

Article information

Article designation	Article description	Colour	KG	SAP article no.
TLM/LL 611-02 SM	Door loudspeaker module Line Level	Silver metallic	E	200087581-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 SM	Touch-up applicator	Silver metallic	0	210007117-00

Door loudspeaker module Line Level TLM/LL 611-02 SM

200087581

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
BTLE 050-.../-03, BTLM 650-..., TLM 611/612-...	Loudspeaker	Others	E	200029074-01
TLM 611/612-02, BTLM 650-04/651-0, ATLM 670/671-0	Microphone	Others	E	210011867-00
TLM 61x-01, BTLM 650-... SM	Light button with light symbol	Silver metallic	E	200029098-00

Door loudspeaker module Line Level
TLM/LL 611-02 SM

200087581

Door loudspeaker module Line Level
TLM/LL 611-02 SM

200087581

TLM/LL 611-02 Door loudspeaker module Line level	Product information	117 kB	Download
TLM/LL 611-...	Declaration of Conformity	255 kB	Download
REACH Information	Additional information	798 kB	Download