



Lock module
SM 611-01 AG
210004992-00

Product description

Lock module with two-stage non-holding contact for accommodating a customer-provided profile half cylinder in accordance with DIN 18252 with a total length of approx. 40 mm. The lock ward can be fixed or adjustable.

Specifications

| | |
|----------------------------|-------------------|
| Contact type: | contact 24 V, 2 A |
| Mounting depth (mm): | 41 |
| Protection system: | IP 54 |
| Ambient temperature: | -20 °C to +55 °C |
| Height of structure (mm): | 9 |
| Dimensions (mm) W x H x D: | 99 x 99 x 50 |

Article information

| Article designation | Article description | Colour/Material | KG SAP article no. |
|---------------------|---------------------|-----------------|--------------------|
| SM 611-01 AG | Lock module | Anthracite grey | B 210004992-00 |


Accessories


| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|---------------------|-----------------|----|-----------------|
| Vario 611 AG | Touch-up applicator | Anthracite grey | 0 | 210007124-00 |

Lock module
SM 611-01 AG

210004992

Page 2





Lock module
SM 611-01 AG

210004992

Page 3

| | | | |
|-----------------------|---------------------------|--------|--------------------------|
| SM 611-01 Lock module | Product information | 536 kB | Download |
| | Declaration of Conformity | 140 kB | Download |
| SM 611-01 | Declaration of Conformity | 333 kB | Download |
| | Additional information | 140 kB | Download |