



Access door  
loudspeaker module  
Plus  
ATLM 671-0 W  
210007344-00

## Product description

Access door loudspeaker module Plus for Siedle Vario with integrated loudspeaker and microphone, as well as additional audio amplifier and noise filter.

### Performance features:

- Front grille made of weather and UV-resistant polycarbonate (via the Access server)
- Loudspeaker, voice volume can be adjusted
- Voice volume can be doubled via the audio amplifier
- Durable electret microphone
- Light button with LED-lit light symbol
- Connection of a ZAM 670-... status display module for optical and acoustic signalling of the operating state is possible
- Acoustic feedback when pressing a call button can be activated

## Specifications

Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54
Height of structure (mm):	9
Dimensions (mm) W x H x D:	99 x 99 x 35

## Article information

Article designation	Article description	Colour/Material	KGSAP article no.
ATLM 671-0 W	Access door loudspeaker module Plus	White	F 210007344-00

## Accessories

Article designation	Article description	Colour/Material	KG	SAP article no.
Vario 611 W	Touch-up applicator	White	0	210007116-00

## Spare parts



Access door  
loudspeaker module  
Plus  
ATLM 671-0 W

210007344

Page 2

Article designation	Article description	Colour/Material	KG	SAP article no.
ATLM 67x-...	Terminal block	Black	E	200029835-00
ATLM/CATLM/SATLM 671-..., BTLM/ CBTLM/SBTLM 651-...	Loudspeaker	Others	E	210011870-00
TLM 611/612-02, BTLM 650-04/651-0, ATLM 670/671-0	Microphone	Others	E	210011867-00
TLM 61x-01, BTLM 650-... W	Light button with light symbol	White	E	200029096-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Access door  
loudspeaker module  
Plus  
ATLM 671-0 W

210007344

Page 3





Access door  
loudspeaker module  
Plus  
ATLM 671-0 W

210007344

Page 4

---

ATLM 671-0 Access door loudspeaker module Plus

ATLM 671-0 Access door loudspeaker module Plus

Product information	499 kB	Download
Declaration of Conformity	1,1 MB	Download
Commissioning instruction	2,2 MB	Download
Commissioning instruction	2 MB	Download
Commissioning instruction	1,8 MB	Download
Additional information	109 kB	Download
System manual	6,4 MB	Download
System manual	6,7 MB	Download