

Smart Gateway
SG 150-0

210007449-00



Product description

Smart Gateway: top hat rail device for private or professional use for smaller systems (up to 10 IP users).

Specifications

| | |
|----------------------------|--|
| Operating voltage: | 20–50 V DC, PoE in accordance with 802.3af |
| Operating current: | max. 400 mA |
| Protection system: | IP 20 |
| Ambient temperature: | 0 °C to +40 °C |
| Horizontal pitch (HP): | 6 |
| Dimensions (mm) W x H x D: | 107 x 109 x 60 |

Article information

| Article designation | Article description | Colour/Material | KG SAP article no. |
|---------------------|---------------------|-----------------|--------------------|
| SG 150-0 | Smart Gateway | Black | D 210007449-00 |

Accessories


| Article designation | Article description | Colour/Material | KG | SAP article no. |
|---------------------|--------------------------------------|-----------------|----|-----------------|
| BLC 250-0 | Bus licence client | Others | S | 200048823-00 |
| BLT 250-0 | Bus licence for telephony connection | Others | S | 210006329-00 |
| BLT 251-0 | Bus licence for telephony connection | Others | S | 210008136-00 |

Smart Gateway
SG 150-0

210007449

Page 2





Smart Gateway
SG 150-0

210007449

Page 3

| | | | |
|--|---|---------|--------------------------|
| | Additional information | 260 kB | Download |
| SG 150-0 Smart Gateway | Product information | 561 kB | Download |
| SG 150-0 Smart Gateway | Declaration of Conformity | 759 kB | Download |
| Siedle Finder SG 150/650-... | Software | 21,9 MB | Download |
| | Commissioning instruction | 1,1 MB | Download |
| | Additional information | 140 kB | Download |
| SG 150-0 Release Notes V 2.2.0 | Release Notes | 179 kB | Download |
| SG 150-0 Release Notes V 2.3.0 | Release Notes | 178 kB | Download |