



Accessory sub-rack
ZGE 601-0

210008465-00

Product description

Accessory sub-rack for operating up to 3 ATLC/NG 670-0 or other Siedle system components in an IT safety cabinet system (482.6 mm / 19") which meets the protection requirements according to EN 62368-1. Space required (height): 133.35 mm / 5.25" / 3 rack units (HE). Delivered pre-assembled and, if equipped it is delivered ready for operation, incl. connected power cable.

Scope of supply

- Pre-mounted ZGE 601-0 sub-rack, partially-equipped (1 x ATLC/NG 670-0)
- Two-pin connecting cable with contour plug/profile plug (CEE 7/17) connected ready for operation for the voltage supply

Technical data

ZGE...:

Dimensions (mm) W x H x D: 483 x 132 x 135 (175 incl. handles)

Top hat rail: 2 x 24 horizontal pitches (TE)

Length of connecting cable (cm): 270

ANG 600-...:

Operating voltage: 100–240 V AC, +/-10 %, 50/60 Hz

Operating current: 0.5– 1 A

Output voltage: 48 V DC

Output current: 800 mA

Fuse: primary thermal fuse, secondary short circuit proof

Protection system: IP 20

Ambient temperature: 0°C to +40°C

Horizontal pitch (TE): 6

Dimensions (mm) W x H x D: 107 x 89 x 60

ATLC 670-...:

Output voltage: 10–16 V AC/DC

Output current: max. 700 mA AC / 300 mA DC

Contact type: NO contact 30 V, 2 A

Protection system: IP 20

Ambient temperature: 0°C to +40°C

Horizontal pitch (TE): 6

Dimensions (mm) W x H x D: 107 x 89 x 60

Specifications

Dimensions (mm) W x H x D:

483 x 132 x 135 (175 incl. handles)

Accessory sub-rack
ZGE 601-0

210008465

Page 2





Accessory sub-rack
ZGE 601-0

210008465

Page 3

ZGE 600/601/602/603-0 Accessory sub-rack	Product information	913 kB	Download
ZGE 600-..., 601-..., 602-..., 603-...	Declaration of Conformity	2,6 MB	Download
REACH Information	Additional information	824 kB	Download
	System manual	8,6 MB	Download