

Siedle IQ HTS
IQ HTS

210009625-00



Product description

In-house telephone for 1+n technology with WLAN interface for mobile extension through the Siedle app.

With the call, speech, door release and light functions on the indoor station and on a smartphone with the Siedle app.

The storey call is also available on the in-house telephone.

Performance features:

- 2.4 GHz WLAN interface for the Siedle app
- Bluetooth 4.2 interface for commissioning
- Another indoor station can be connected in parallel
- Integrated door release and light button
- Integrated audio privacy function
- Call volume up to max. 83 dB(A)
- Automatic update function when Internet connection is active
- The Siedle app behaves like an indoor device connected in parallel for the call

Specifications

Operating voltage:	12–30 V DC
Operating current:	max. 300 mA
Ambient temperature:	+5 °C to +40 °C
Dimensions (mm) W x H x D:	91 x 201 x 48

Article information

Article designation	Article description	Colour/Material	KG SAP article no.
IQ HTS	Siedle IQ HTS	White	D 210009625-00

Accessories

Article designation	Article description	Colour/Material	KG	SAP article no.
HH 800-0	Hearing aid-compatible receiver	White	E	200087165-00
HT/NB 800-0 W	In-house telephone retrofit panel	White	D	210008889-00
NEO006.0-I-X-12	Power supply unit	Black	D	210010421-00
PSM 1 12 24	Line rectifier	Others	D	210010340-00
ZTS 800-01 W	Standard table-top accessory	White	A	200044472-00



Siedle IQ HTS
IQ HTS

210009625

Page 2

Spare parts

Article designation	Article description	Colour/Material	KG	SAP article no.
HT 811/840/850/870-... W	Receiver with no-tangle cord	White	E	200029573-00
HTS 811-...	Terminals	Grey	E	200029589-00
IQ BTS/HTA/HTS	Terminals	Others	E	210008887-00

Siedle IQ HTS

IQ HTS

210009625

Page 3





Siedle IQ HTS
IQ HTS

210009625

Page 4

Siedle IQ HTS	Product information	959 kB	Download
HTS 811-0 Standard In-House Telephone	Product information	1,1 MB	Download
Siedle IQ HTS	Manual	467 kB	Download
IQ HTS	Declaration of Conformity	1,2 MB	Download
	Additional information	140 kB	Download