



Secure Controller
SC 600-0

210010591-00

Product description

Secure Controller as the central controller for managing access rights in private buildings and commercial properties.

Performance features:

- 2 RS485 interfaces
- 4 doors per controller
- Protocol OSDP / Vario Bus
- Max. 500,000 users
- Max. 16 modules per controller
- Max. 64 controllers can be networked
- Log for 1,000,000 events
- Programming via web interface
- Wizard for easy commissioning

Specifications

Operating voltage:	PoE in accordance with 802.3af (PoE class 3), 14–28 V DC
Operating current:	max. 115 mA
Contact type:	4 changeover switches 30 V DC, 10 A
Protection system:	IP 20
Ambient temperature:	0 °C to +40 °C
Dimensions (mm) W x H x D:	140 x 215 x 50

Article information

Article designation	Article description	Colour/Material	KG SAP article no.
SC 600-0	Secure Controller	White	D 210010591-00

Secure Controller
SC 600-0

210010591

Page 2





Secure Controller
SC 600-0

210010591

Page 3

SC 600-0 Secure Controller	Product information	534 kB	Download
SC 600-0 Secure Controller	Declaration of Conformity	743 kB	Download
Tech Tool SC 600-0	Software	3,4 MB	Download
Sample file user administration SC 600	Programming template	0,4 kB	Download
	Commissioning instruction	1,6 MB	Download
Firmware SC 600-0 V 2.12.7	Firmware	15,2 MB	Download
	Additional information	140 kB	Download
	System manual	6,7 MB	Download