

Access server hardware
ASH 671-01 S
210010595-01



Product description

Access Server hardware S for the IP-based building communication system Siedle Access Professional for up to 50 users. The Access Professional basic licence is required for standard operation – 10 users are included. Additional users/functions can be added to the system by purchasing further user or application licences.

Components:

CPU: Intel Celeron J6412
Working memory: 4 GB DDR4
Graphic: Onboard (2 x DP, 1 x HDMI)
Hard disc: 120 GB M.2 SATA SSD
LAN: 3 x gigabit (2.5GbE)
USB: 3 x USB 3.0, 3 x USB 2.0

Version in a compact desktop metal housing.

Specifications

Operating voltage:	100–240 V AC, 50–60 Hz
Typical current consumption:	10 W (max. 18 W)
Ambient temperature:	0 °C to +40 °C
Dimensions (mm) W x H x D:	150 x 45 x 127

Accessories

Article designation	Article description	Colour	KG	SAP article no.
ALFA 270-0	Access licence for connecting a non-Siedle device	Others	S	200042253-00
ALFC 270-0	Access licence non-Siedle device IP camera	Others	S	210011712-00
ALFM 270-0	Access licence function module	Others	S	210011713-00
ALKNX 270-0	Access licence for KNX gateway	Others	S	210009245-00
ALSA 270-0	Access licence for Siedle app	Others	S	210010209-00
ALT 270-0	Access licence for telephony connection	Others	S	200042271-00
ALU 670-0	Access licence upgrade	Others	S	210010621-00
APR 670-0 10	Access Professional	Others	S	210005979-00
APR 670-0 B	Access Professional basic licence	Others	S	210010598-00

Access server hardware
ASH 671-01 S

210012372

Page 2



Article designation

ASC 170-0

ASHT 170-0

Article description

Access Software Concierge

Access Software In-house telephone

Colour

Others

Others

KG

S

S

**SAP article
no.**

200042276-00

200042275-00

Access server hardware
ASH 671-01 S

210012372

Page 3





Access server hardware
ASH 671-01 S

210012372

Page 4

ASH 671-01 S Access server hardware
ASH 671-01 S

Product information	523 kB	Download
Declaration of Conformity	569 kB	Download
Commissioning instruction	2,2 MB	Download
Additional information	420 kB	Download
System manual	8 MB	Download