

Secure Extension
SE 600-0

210011276-00



Product description

Secure Extension as an extension for the Secure Controller. Up to 4 Extensions can be connected per Controller.

Performance features:

- RS485 interfaces
- 4 relays per Extension
- 2 inputs per door (status/button)
- OSDP protocol
- max. 4 Extensions per Controller (2 pro RS485 interface) *
- LED status display

Specifications

| | |
|----------------------------|---------------------------------|
| Contact type: | 4 changeover switches 30 V, 2 A |
| Protection system: | IP 20 |
| Ambient temperature: | 0 °C to +40 °C |
| Horizontal pitch (HP): | 6 |
| Dimensions (mm) W x H x D: | 107 x 89 x 60 |

Secure Extension
SE 600-0

210011276

Page 2





Secure Extension
SE 600-0

210011276

Page 3

| | | | |
|--|---|---------|--------------------------|
| SE 600-0 Secure Extension | Product information | 718 kB | Download |
| SE 600-0 Secure Extension | Declaration of Conformity | 355 kB | Download |
| REACH Information | Additional information | 798 kB | Download |
| Firmware SE 600-0 V 1.50.0 | Firmware | 18,7 kB | Download |
| OSDP Config Tool (DE/EN) | Software | 1 MB | Download |