SSS SIEDLE

Bus door loudspeaker
for Siedle Vario
BTLM 750-0 AG

210011512-00

Product description

Bus door loudspeaker for Siedle Vario with integrated loudspeaker and microphone. Easy cabling thanks to pre-assembled, plug-in cable connection.

Performance features:
- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone
- Potential-free work contact for door release, can be controlled without additional wiring via existing bus line
- Button acknowledgement tone, can be deactivated on the door loudspeaker
- Nameplate lighting for the call buttons can be switched off
- Integrated camera control
- A COM 611-… code lock module and/or DRM 612-… display call module for digital call input can be connected

Specifications

Contact type:	Contact 15 V AC, 30 V DC, 2 A
Switching time:	DR, 3 sec
Ambient temperature:	–20 °C to +55 °C
Protection system:	IP 54, IK 09
Height of structure (mm):	1.4
Dimensions (mm) W x H x D:	99 x 99 x 25

Article information

Article designation	Article description	Colour	KGSAP article no.
BTLM 750-0 AG	Bus door loudspeaker for Siedle Vario	Anthracite grey	A 210011512-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 AG	Touch-up applicator	Anthracite grey	0	210007124-00
ZVK/BRMA 050/300	Connecting cable BTLM 750-… to BRMA 050-…, 300 mm	Others	E	210011994-00

Bus door loudspeaker
for Siedle Vario
BTLM 750-0 AG

210011512

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
BTLM 750-…	Door loudspeaker connecting cable BTLM 750-…	Others	E	210011960-00
BTLM 750-…	Microphone	Others	E	210011961-00
BTLM 750-…	Terminal block	Others	E	210011959-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Bus door loudspeaker
for Siedle Vario
BTLM 750-0 AG

210011512

Bus door loudspeaker
for Siedle Vario
BTLM 750-0 AG

210011512

BTLM 750-0 Bus door loudspeaker for Siedle Vario	Product information	596 kB	Download
BTLM 750-...	Declaration of Conformity	354 kB	Download
REACH Information	Additional information	798 kB	Download