



Bus door loudspeaker
for Siedle Vario
BTLM 750-0 SM

210011514-00

Product description

Bus door loudspeaker for Siedle Vario with integrated loudspeaker and microphone. Easy cabling thanks to pre-assembled, plug-in cable connection.

Performance features:

- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone
- Potential-free work contact for door release, can be controlled without additional wiring via existing bus line
- Button acknowledgement tone, can be deactivated on the door loudspeaker
- Nameplate lighting for the call buttons can be switched off
- Integrated camera control
- A COM 611-... code lock module and/or DRM 612-... display call module for digital call input can be connected

Specifications


Contact type:	Contact 15 V AC, 30 V DC, 2 A
Switching time:	DR, 3 sec
Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54, IK 09
Height of structure (mm):	1.4
Dimensions (mm) W x H x D:	99 x 99 x 25

Article information

Article designation	Article description	Colour	KGSAP article no.
BTLM 750-0 SM	Bus door loudspeaker for Siedle Vario	Silver metallic	A 210011514-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 SM	Touch-up applicator	Silver metallic	0	210007117-00
ZVK/BRMA 050/300	Connecting cable BTLM 750-... to BRMA 050-..., 300 mm	Others	E	210011994-00



Bus door loudspeaker
for Siedle Vario
BTLM 750-0 SM

210011514

Page 2

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
BTLM 750-...	BTLM 750-... door loudspeaker connecting cable	Others	E	210011960-00
BTLM 750-...	Microphone	Others	E	210011961-00
BTLM 750-...	Terminal block	Others	E	210011959-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Bus door loudspeaker
for Siedle Vario
BTLM 750-0 SM

210011514

Page 3





Bus door loudspeaker
for Siedle Vario
BTLM 750-0 SM

210011514

Page 4

BTLM 750-0 Bus door loudspeaker for Siedle Vario
BTLM 750-...

Product information

596 kB

[Download](#)

Declaration of Conformity

354 kB

[Download](#)

Additional information

109 kB

[Download](#)