



Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 AG
210011522-00

Product description

Access camera door loudspeaker for Siedle Vario with integrated camera, loudspeaker and microphone. Automatic day/night switchover (true day/night) and integrated infrared lighting. Horizontal/vertical pick-up angle: approx. 130°/100°. Easy cabling thanks to pre-assembled, plug-in cable connection.

Performance features:

- LAN interface: RJ-45, 10/100 Mbits
- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone, microphone sensitivity can be adjusted
- Audio codec: G.722
- Button acknowledgement tone
- Nameplate illumination of the call buttons can be controlled (time controlled or demand-driven)
- Image format: 16:9
- Video codec: H.264, MJPEG
- Resolution: 1280 x 720 (HD), 352 x 288 (CIF)
- Image pick-up: CMOS sensor 1/2.7" 1920 x 1080 pixels
- Wide Dynamic Range (WDR)

Specifications

Operating voltage:	PoE in accordance with 802.3af
Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54, IK 07
Height of structure (mm):	3.5
Dimensions (mm) W x H x D:	99 x 99 x 35

Article information

Article designation	Article description	Colour	KG&SAP article no.
ACTLM 770-0 AG	Access camera door loudspeaker for Siedle Vario	Anthracite grey	F 210011522-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 AG	Touch-up applicator	Anthracite grey	0	210007124-00



Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 AG

210011522

Page 2

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
Vario 611	Sealing frame modules	Grey	E	210007484-00



Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 AG

210011522

Page 3





Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 AG

210011522

Page 4

ACTLM 770-0 Access camera door loudspeaker for Siedle Vario	Product information	844 kB	Download
	Commissioning instruction	2 MB	Download
	Additional information	109 kB	Download
	System manual	8,3 MB	Download