



Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 W
210011525-00

Product description

Access camera door loudspeaker for Siedle Vario with integrated camera, loudspeaker and microphone. Automatic day/night switchover (true day/night) and integrated infrared lighting. Horizontal/vertical pick-up angle: approx. 140°/70°. Easy cabling thanks to pre-assembled, plug-in cable connection.

Performance features:

- LAN interface: RJ45, 10/100 Mbits
- Front grille made of weather and UV-resistant polycarbonate
- Loudspeaker, voice volume can be adjusted
- Durable electret microphone, microphone sensitivity can be adjusted
- Audio codec: G.722
- Button acknowledgement tone
- Nameplate illumination of the call buttons can be controlled (time controlled or demand-driven)
- Image format: 16:9
- Video codec: H.264, MJPEG
- Resolution: 1280 x 720 (HD), 352 x 288 (CIF)
- Image pick-up: CMOS sensor 1/2.7" 1920 x 1080 pixels
- Wide Dynamic Range (WDR)

Specifications

Operating voltage:	PoE in accordance with 802.3af
Ambient temperature:	-20 °C to +55 °C
Protection system:	IP 54, IK 07
Height of structure (mm):	3.5
Dimensions (mm) W x H x D:	99 x 99 x 35

Article information

Article designation	Article description	Colour	KGSAP article no.
ACTLM 770-0 W	Access camera door loudspeaker for Siedle Vario	White	F 210011525-00



Access camera door
loudspeaker for Siedle
Vario

ACTLM 770-0 W

210011525

Page 2





Access camera door
loudspeaker for Siedle
Vario
ACTLM 770-0 W

210011525

Page 3

ACTLM 770-0 Access camera door loudspeaker for Siedle Vario	Product information	847 kB	Download
ACTLM 770-0	Declaration of Conformity	352 kB	Download
	Commissioning instruction	2,4 MB	Download
REACH Information	Additional information	824 kB	Download
	System manual	8,6 MB	Download