

Bus camera 180 for  
Siedle Vario  
BCM 758-0 AG  
210012154-00

## Product description

Bus camera 180 for Siedle Vario with automatic day/night switchover (True Day/Night) and integrated infrared lighting. Horizontal/vertical pick-up angle: approx. 175°/120°. Easy cabling thanks to pre-assembled, plug-in cable connection.

Full screen or 9 picture excerpts can be selected  
Electronic image rectification in full screen  
Extended pick-up angle in edge area for selected picture excerpt  
Backlight compensation (BLC)  
Wide Dynamic Range (WDR)  
Colour system: PAL  
Image pick-up: CMOS sensor 1/2.7" 1920 x 1080 pixels  
Resolution: 600 TV lines  
Lens: 1.55 mm  
2-step heating: 12 V AC max. 130 mA

## Specifications

Protection system:	IP 54, IK 10
Ambient temperature:	-20 °C to +55 °C
Height of structure (mm):	15
Dimensions (mm) W x H x D:	99 x 99 x 41

## Article information

Article designation	Article description	Colour	KGSAP article no.
BCM 758-0 AG	Bus camera 180 for Siedle Vario	Anthracite grey	D 210012154-00

## Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 AG	Touch-up applicator	Anthracite grey	0	210007124-00
ZAK/BCM 750	Camera connecting cable for BCM 753/758-...	Others	E	210012357-00
ZVK/BCM 750/500	Connecting cable BCM 753/758-... to BTLM 750-..., 500 mm	Others	E	210012356-00



Bus camera 180 for  
Siedle Vario  
BCM 758-0 AG

210012154


Page 2

---

## Spare parts

---

Article designation	Article description	Colour	KG	SAP article no.
ACM 671/673/678-..., BCM 65x-..., CM 61x-...	Glass cover	Clear glass	E	200048697-00
ACM 671/673/678-..., BCM 65x-..., CM 61x-... AG	Screen frame	Anthracite grey	E	210005930-00
BCM 753/758-...	Connecting cable BCM 753/758-... to BTLM 750-..., 300 mm	Others	E	210012355-00
Vario 611	Sealing frame modules	Grey	E	210007484-00




Bus camera 180 for  
Siedle Vario  
BCM 758-0 AG

210012154

Page 3





Bus camera 180 for  
Siedle Vario  
BCM 758-0 AG

210012154

Page 4

---

Bus camera 130/180  
BCM 758-...

Product information

793 kB

[Download](#)

Declaration of Conformity

352 kB

[Download](#)

Additional information

420 kB

[Download](#)