SSS SIEDLE



Bus camera 180 for
Siedle Vario
BCM 758-0 DG

210012155-00

Product description

Bus camera 180 for Siedle Vario with automatic day/night switchover (True Day/Night) and integrated infrared lighting. Horizontal/vertical pick-up angle: approx. 175°/120°. Easy cabling thanks to pre-assembled, plug-in cable connection.

Full screen or 9 picture excerpts can be selected
Electronic image rectification in full screen
Extended pick-up angle in edge area for selected picture excerpt
Backlight compensation (BLC)
Wide Dynamic Range (WDR)
Colour system: PAL
Image pick-up: CMOS sensor 1/2.7" 1920 x 1080 pixels
Resolution: 600 TV lines
Lens: 1.55 mm
2-step heating: 12 V AC max. 130 mA

Specifications

Protection system:	IP 54, IK 10
Ambient temperature:	–20 °C to +55 °C
Height of structure (mm):	15
Dimensions (mm) W x H x D:	99 x 99 x 41

Article information

Article designation	Article description	Colour	KGSAP article no.
BCM 758-0 DG	Bus camera 180 for Siedle Vario	Micaceous dark grey	D 210012155-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
Vario 611 DG	Touch-up applicator	Micaceous dark grey	0	210007123-00
ZAK/BCM 750	Camera connecting cable for BCM 753/758-…	Others	E	210012357-00
ZVK/BCM 750/500	Connecting cable BCM 753/758-… to BTLM 750-…, 500 mm	Others	E	210012356-00

Bus camera 180 for
Siedle Vario
BCM 758-0 DG

210012155

Spare parts

Article designation	Article description	Colour	KG	SAP article no.
ACM 671/673/678-..., BCM 65x-..., CM 61x-...	Glass cover	Clear glass	E	200048697-00
ACM 671/673/678-..., BCM 65x-..., CM 61x-... DG	Screen frame	Micaceous dark grey	E	200048701-00
BCM 753/758-…	Connecting cable BCM 753/758-… to BTLM 750-…, 300 mm	Others	E	210012355-00
Vario 611	Sealing frame modules	Grey	E	210007484-00

Bus camera 180 for
Siedle Vario
BCM 758-0 DG

210012155

Bus camera 180 for
Siedle Vario
BCM 758-0 DG

210012155

Bus camera 130/180	Product information	793 kB	Download
BCM 758-...	Declaration of Conformity	352 kB	Download
REACH Information	Additional information	798 kB	Download