


Siedle Axiom In-Home
A 150-10 R

210012175-00



Product description

Siedle Axiom In-Home the video indoor station with 7" touchscreen for the Siedle In-Home bus. With the functions calling, speech, vision, door release, light, storey call/switching/control functions, message displays and internal communication.

Planning note: The flat height of only 18 mm requires a double flush-mounted box for installation, which is not included in the scope of delivery.

Performance features:

- 17.8 cm (7") touchscreen, resolution 1024 x 600 pixel
- 2 buttons for quick and intuitive operation of the door functions
- Input terminals for storey call buttons
- Integrated switching relay for external signalling device in the case of door call or manual switching function
- Transfer of the device configuration from the bus programming software using SD card
- All the convenience functions of the Siedle In-Home bus can be used (see In-Home bus system manual: video)
- 15 switching functions and 15 messages in conjunction with the BSM/BSE bus switching module or BEM bus input module via BPS
- Selective dialling of door loudspeakers/cameras
- Integrated audio and video privacy function
- Parallel switching of max. 8 indoor stations
- Intuitive operating interface with situational user interfaces
- Main screen with navigation and tiles for switching functions/messages
- Favourites can be defined for quick operation when there is a door call
- Data protection-compliant video memory function
- Message history with date and time
- Voice volume and call volume can be adjusted in 5 stages
- Full screen display for the door video can be selected while a call is active
- Ring tone muting and status display
- Call differentiation for 2 door calls, 3 group calls, storey call, internal call
- Call generator with 11 ring tone sequences, including chime

After the last sale to specialist dealers, Siedle guarantees software and firmware maintenance for a period of 8 years.

Specifications

Operating voltage:	20–30 V DC
Operating current:	max. 300 mA
Contact type:	potential-free S1/S1 max. 15 V AC, 30 V DC, 1 A switching time 1 sec - 19 min



Siedle Axiom In-Home
A 150-10 R

210012175

Page 2

Ambient temperature:

+5 °C to +40 °C

Dimensions (mm) W x H x D:

185 x 144 x 18

Article information

Article designation	Article description	Colour	KG	SAP article no.
A 150-10 R	Siedle Axiom In-Home	Pearl ruby red	D	210012175-00

Accessories

Article designation	Article description	Colour	KG	SAP article no.
ZTA 150-0 R	Table-top accessory for Siedle Axiom In-Home	Pearl ruby red	D	210012301-00


Spare parts

Article designation	Article description	Colour	KG	SAP article no.
A 150-10	Terminals	Others	E	210013277-00
A 150-10	Wall mounting plate	Others	E	210013278-00

Siedle Axiom In-Home
A 150-10 R

210012175

Page 3





Siedle Axiom In-Home
A 150-10 R

210012175

Page 4

A 150-10 Siedle Axiom In-Home	Product information	1,1 MB	Download
	Manual	492 kB	Download
A 150-10	Declaration of Conformity	371 kB	Download
	Additional information	420 kB	Download
A 150-10 Release Notes V 1.0.0 (DE/EN)	Release Notes	165 kB	Download
	Firmware	2,4 MB	Download
A 150-10	Additional information	551 kB	Download