

IQ Door  
IQDS-0

210012905-00



## Product description

IQ Door - Video door station for surface mounting with 1 - 3 call buttons for the Siedle IQ system. Operating mode adjustable: LAN (PoE) or WLAN (external power supply).

### Performance features:

#### Audio

- Loudspeaker, adjustable voice volume
- Long-life electret microphone
- Audio codec: G.722

#### video

- Image sensor: CMOS sensor 1/2.7" 1920 x 1080 pixels
- Horizontal/vertical angle of coverage: approx. 140°/70°
- Picture format: 16:9
- Video codec: MJPEG
- Wide Dynamic Range (WDR)
- Automatic day/night switching (True Day/Night)
- Integrated infrared illumination

#### Connectivity

- LAN interface: RJ45, 10/100 Mbits
- WLAN interface: 2.4 GHz (Wi-Fi 4 / IEEE 802.11n)

#### Operation

- LED status display for call set-up
- Nameplate illumination of the call buttons

#### Installation and housing

- Metal housing
- Name plates can be changed at the front

## Specifications

Operating voltage:	48 V DC, PoE in accordance with 802.3af (PoE class 0)
Operating current:	max. 270 mA
Contact type:	Contact 15 V AC, 30 V DC, 2 A
Protection system:	IP 54
Ambient temperature:	-20 °C to +55 °C
Dimensions (mm) W x H x D:	110 x 226 x 37.5

## Article information



IQ Door  
IQDS-0

210012905

Page 2

Article designation	Article description	Colour	KG	SAP article no.
IQDS-0	IQ Door	Matt chrome	D	210012905-00

## Accessories

Article designation	Article description	Colour	KG	SAP article no.
ZBIQDS 1	Narrow accessory cover	Matt chrome	E	210013740-00
ZBIQDS 2	Wide accessory cover	Matt chrome	E	210013741-00

## Spare parts


Article designation	Article description	Colour	KG	SAP article no.
IQDS-...	Nameplate superstructure	Others	E	210013743-00
IQDS-..., IQDM-...	Siedle security key	Others	E	210013841-00

IQ Door  
IQDS-0

210012905

Page 3





IQ Door  
IQDS-0

210012905

Page 4

---

IQDS-0 / IQDM-0 IQ Door	Product information	2,2 MB	Download
WLAN Usage Information Siedle IQ	Additional information	312 kB	Download
IQDM-0	Declaration of Conformity	605 kB	Download
REACH Information	Additional information	824 kB	Download